



USSLT

45 Railroad Avenue, Manahawkin, NJ, 08050
 Website: www.usslt.com Tel.: 609-339-9417 / 609-781-9291

Features & Benefits:

- 1) 10 year 100,000 hour warranty
- 2) IP65 rating.

Certificates & Reports:

IES files available.
 Certificates:

Applications:

Suitable for factory, yard, parking lot, billboard, etc.



IP66 US II LED Flood Light (Nichia chip+Sosen driver)

Model No.	Picture	Power	Luminous Flux	Dimmable	Input Voltage	LED Type/ Driver Brand	CCT	Material	Beam Angle	Product Dimension	MSRP Installed
US02-50		50W	6,000lm	NO	100-277VAC, 50/60Hz	Nichia chip Sosen driver	5000K	ALU Alloy+ Glass cover	120°, 75°x100°	280x269x74mm	Call
US02-70		70W	8,400lm							280x269x74mm	Call
US02-90		90W	10,800lm							280x269x74mm	Call

IP66 US II LED Flood Light (Nichia chip+Meanwell driver) (UL DLC Listed)

Model No.	Picture	Power	Luminous Flux	Dimmable	Input Voltage	LED Type/ Driver Brand	CCT	Material	Beam Angle	Product Dimension	MSRP Installed
US02-50		50W	6,000lm	NO	100-277VAC, 50/60Hz	Nichia chip Meanwell driver	5000K	ALU Alloy+ Glass cover	120°, 75°x100°	280x269x74mm	Call
US02-70		70W	8,400lm							280x269x74mm	Call

Standard CCT: 5000K (4000K, 3000K optional)
 Standard CRI: 73 (CRI>80 optional)
 75°x100° version costs \$12/pc extra.

IP65 US III LED Flood Light (Epistar chip+Upshine driver)

Model No.	Picture	Power	Luminous Flux	Dimmable	Input Voltage	LED Type/ Driver Brand	CCT	Material	Beam Angle	Product Dimension	MSRP Installed
US03-10		10W	1,000lm	NO	100-277VAC, 50/60Hz	Epistar chip Upshine driver	5000K	ALU Alloy+ Glass cover	90°	149x121x43mm	Call
US03-20		20W	2,000lm							179x138x50mm	Call
US03-30		30W	3,000lm							202x157x51mm	Call

Standard CCT: 5000K (3000K, 4000K optional)
 Standard CRI: 73 (CRI>80 optional)







IP65 US IV LED Flood Light (Epistar chip+Upshine driver)

Model No.	Picture	Power	Luminous Flux	Dimmable	Input Voltage	LED Type/ Driver Brand	CCT	Material	Beam Angle	Product Dimension	MSRP Installed
US04-010		10W	1,150lm	NO	100-277VAC, 50/60Hz	Epistar chip/ Upshine driver	5000K	ALU Alloy+ Glass cover	120°	163x143x42mm	Call
US04-030		30W	3,700lm							287x238x48mm	Call
US04-050		50W	5,800lm							350x281x59mm	Call

Standard CCT: 5000K (3000K, 4000K optional)
 Standard CRI: 73 (CRI>80 optional)

Accessories:

Part No.	Picture	Description	MSRP Installed
CC-A00-01		IP65 cable connector	Call
PG-A00-01		EU plug	Call
PG-A00-02		AU plug	Call
PG-A00-03		US plug	Call

Notes:

1. Quantity price if installation is not required upon request
2. Payment Term: 60% down, 20% on delivery, 20% on day of completion, If no installation, 40% when tracking # is given
3. Lead time: 7-10 days for small orders, 15-20 days for larger orders
4. **100% Money-Back Guarantee**