



USSLT LED Flat Panel Light

Model No.	Picture	Trim Color	Power	Voltage	PF	CCT	LED	Beam angle	Lumen	Size	Packing(c m)	MSRP Installed
US-PL2X2-40W		White	40W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	3400-3520LM	603*603*10mm	69*32*70 4PCS 26KG	Call
US-PL2X2-40WD		White	40W	100-277V 0-10V DIM	>0.9	2700K 3000K 4000K 5000K	SMD	120	3400-3520LM			Call
US-PL2X2-50W		White	50W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM	603*603*10mm	69*32*70 4PCS 26KG	Call
US-PL2X2-50WD		White	50W	100-277V 0-10V DIM	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM			Call
US-PL1X4-40W		White	40W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	3400-3520LM	303*1213*10mm	130*33*40 4PCS 27KG	Call
US-PL1X4-40WD		White	40W	100-277V 0-10V DIM	>0.9	2700K 3000K 4000K 5000K	SMD	120	3400-3520LM			Call
US-PL1X4-50W		White	50W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM	303*1213*10mm	130*33*40 4PCS 27KG	Call
US-PL1X4-50WD		White	50W	100-277V 0-10V DIM	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM			Call
US-PL2X4-50W		White	50W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM	603*1213*10mm	130*18*70 2PCS 25KG	Call
US-PL2X4-50WD		White	50W	100-277V 0-10V DIM	>0.9	2700K 3000K 4000K 5000K	SMD	120	4250-4400LM			Call
US-PL2X4-60W		White	60W	100-277V	>0.9	2700K 3000K 4000K 5000K	SMD	120	5100-5280LM	603*1213*10mm	130*18*70 2PCS 25KG	Call
US-PL2X4-60WD		White	60W	100-277V 0-10V DIM	>0.9		SMD	120	5100-5280LM			Call
US-PL2X4-80WD		White	80W	100-277V 0-10V DIM	>0.9		SMD	120	6400-6800LM			Call

DLC V4.0 + USD2.0/pc, 100lm/w

Surface mounting fixture			Used for 2x2ft Panel	Call	Call
			Used for 1x4ft Panel	Call	Call
			Used for 2x4ft Panel	Call	Call
suspension installation			Used for 2x2ft Panel	Call	Call
			Used for 1x4ft Panel	Call	Call
			Used for 2x4ft Panel	Call	Call
Hook			Used for 2x2ft Panel	Call	Call
			Used for 1x4ft Panel	Call	Call
			Used for 2x4ft Panel	Call	Call